

American Lubricating Co
500 SOUTH FRONT STREET * PO BOX 258
MEMPHIS, TN 38101 USA
www.americanlubricating.com
phone: 901 527 4707 fax: 901 525 7670

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:
American Lubricating Company
ADDRESS:
PO Box 258, Memphis, TN 38101

PRODUCT NAME: No Smoke Two Stroke
2 Cycle Engine Oil
/Fuel Stabilizer
HAZARD MATERIAL ID SYSTEM: H-1 F-1 R-0 PP-B

SECTION 1 - DESCRIPTION

PRODUCT NAME: No Smoke Two Stroke Two Cycle Engine Oil w/Fuel Stabilizer
DOT SHIPPING NAME: N/A
DOT HAZARD CLASS: Non-Hazardous
CAS REGISTRY NUMBER: 64742-54-7 or 64742-65-0
CHEMICAL NAME: Petroleum lubricating oil and fuel additive containing a polyamine condensation product based dispersant and other component judged not to affect the potential health or environmental impact of the product, and <1% proprietary fuel stabilizer.
PREPARER: Chip Armstrong, October 2002

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENTS: Blend of mineral oil, light distillate solvent, and proprietary additives.

SECTION 3 - PHYSICAL DATA

BOILING POINT, DEG F: N/A
MELTING POINT, DEG F: N/A
SPECIFIC GRAVITY: 0.88
APPEARANCE: Dyed blue

VAPOR PRESSURE: negligible
VAPOR DENSITY: above 1
SOLUBILITY IN WATER: negligible
ODOR: mineral oil

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT, DEG F: 178
EXTINGUISHING MEDIUM: water fog, foam, dry chemical, carbon dioxide
SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool exposed containers
Fire fighting personnel should use respiratory protection.
UNUSUAL FIRE EXPLOSION HAZARDS: product of combustion includes fumes & CO2

SECTION 5 - REACTIVITY HAZARDS

STABILITY: stable
HAZARDOUS POLYMERIZATION: will not
HAZARDOUS DECOMPOSITION PRODUCTS: carbon monoxide upon combustion, fumes, smoke

MATERIAL TO AVOID: strong oxidizers
CONDITION TO AVOID: flame, extreme heat

SECTION 6 - HEALTH HAZARD INFORMATION

ROUTE OF ENTRY: INHALATION SKIN INGESTION

ACUTE OVEREXPOSURE: may cause reversible eye and skin irritation; prolonged skin exposure may cause dermatitis; ingestion may cause cramps & diarrhea; breathing mists may cause dizziness

CHRONIC OVEREXPOSURE: defined by IARC as Class I mineral oil

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:

NATIONAL TOXICOLOGY PROGRAM IARC MONOGRAPHS OSHA
 YES NO YES NO YES NO

THRESHOLD LIMIT VALUE: 5-mg/cubic meter as mist

EMERGENCY AND FIRST AID: in all cases remove source of exposure

1. INHALATION: unlikely to occur except as mist
2. EYES: flush with water for at least 15 minutes or until irritation subsides
3. SKIN: wash well with soap and water; remove oil soaked clothing; wash clothes before reuse; if irritation develops, consult physician
4. INGESTION: DO NOT induce vomiting; consult physician; contains solvent

SECTION 7 - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: normally not required with adequate ventilation; if exposure exceeds limits, use NIOSH/MSHA approved air respirator

VENTILATION: if mists are present, provide adequate ventilation to control level below the Permissible Exposure Limit

PROTECTIVE GLOVES: impermeable gloves EYE PROTECTION: goggles

OTHER: none usually required

SECTION 8 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

HANDLING & STORAGE PRECAUTIONS: Keep away from fire, flame & sparks

OTHER PRECAUTIONS: never wear oil soaked clothing; discard oil soaked shoes; affix proper warning labels on containers according to 29 CFR 1010.1200

IN CASE OF SPILLS: no unusual hazard; use pump and/or oil absorbent; keep from entering waterways and sewers

WASTE DISPOSAL METHODS: dispose according to current local, state and federal regulations; consider recycling; NOTE: material may become a hazardous waste through use

NOTE: The above information is based on data of which we are aware and is believed to be correct. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. American Lubricating Company, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, we assume no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if

reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.