

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)  
Date of issue: 05/06/2015 Revision date: 06/24/2015  
Version: 2.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: customer\_service@laco.com



### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification in accordance with the Globally Harmonized Standard

Not classified

### 2.2. Label elements

#### GHS labelling

No labelling applicable

### 2.3. Other hazards

### 2.4. Unknown acute toxicity (GHS)

51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	% (w/w)	GHS classification
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulfonate]	(CAS No) 1103-38-4	2.3 Red	Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 3, H412
Iron oxide red	(CAS No) 1309-37-1	2.15 Red	Aquatic Chronic 2, H411
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7	0.67 Purple	Skin Sens. 1, H317

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.
First-aid measures after skin contact	: Wash with plenty of soap and water.
First-aid measures after eye contact	: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : No significant signs or symptoms indicative of any health hazard are expected to occur.

### 4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.  
Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : No particular fire or explosion hazard.  
Reactivity : No dangerous reactions known.

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid creating or spreading dust.

#### 6.1.1. For non-emergency personnel

Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Where excessive dust may result, use approved respiratory protection equipment.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Do not discharge into drains or the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Avoid generating dust. Contain and collect as any solid.  
Methods for cleaning up : Minimize generation of dust. On land, sweep or shovel into suitable containers.

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong acids. Strong oxidizers. Strong bases.  
Storage area : Store in dry, cool, well-ventilated area.

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### 7.3. Specific end use(s)

Marking.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green		
ACGIH	Not applicable	
OSHA	Not applicable	
barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)		
ACGIH	Not applicable	
OSHA	Not applicable	
Iron oxide red (1309-37-1)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	Pneumoconiosis
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Fer, trioxyde de, fumées et poussières (exprimée en Fe)) 10 mg/m <sup>3</sup> (Rouge)
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

### 8.2. Exposure controls

Appropriate engineering controls	: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use.
Eye protection	: No special eye protection equipment recommended under normal conditions of use. In case of dust production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: wax like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 60 - 85 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 177 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: > 1 Specific Gravity
Solubility	: insoluble in water.

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Log Pow	: < 1
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 0 %
-------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Not classified

#### LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

LD50 oral rat	> 5000 mg/kg (yellow)
---------------	-----------------------

#### barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)

LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4.13 mg/l/4h
ATE CLP (vapours)	4.130 mg/l/4h
ATE CLP (dust,mist)	4.130 mg/l/4h

#### Iron oxide red (1309-37-1)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

#### 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m <sup>3</sup> 4 h

**Skin corrosion/irritation** : Not classified

**Serious eye damage/irritation** : Not classified

**Respiratory or skin sensitisation** : Not classified.

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : Not classified.

#### Iron oxide red (1309-37-1)

IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class

**Reproductive toxicity** : Not classified

**Specific target organ toxicity (single exposure)** : Not classified

**Specific target organ toxicity (repeated exposure)** : Not classified

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

**Aspiration hazard** : Not classified  
**Potential adverse human health effects and symptoms**  
Likely routes of exposure : Skin and eye contact;Inhalation

### SECTION 12: Ecological information

#### 12.1 Toxicity

<b>barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)</b>	
LC50 fish 1	50 mg/l 48 h
EC50 Daphnia 1	> 3.8 mg/l 48 h
<b>Iron oxide red (1309-37-1)</b>	
EC50 Daphnia 1	> 100 mg/l
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

#### 12.2. Persistence and degradability

<b>barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)</b>	
Persistence and degradability	Not readily biodegradable. Product persists.
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

#### 12.3. Bioaccumulative potential

<b>LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green</b>	
Log Pow	< 1
<b>barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)</b>	
BCF fish 1	1.7 - 1.8 mg/l .3 mg/l conc. in enviro/dose
Log Pow	-0.67 - 1.07
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
BCF fish 1	53 l/kg
Log Pow	1.28

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.  
Sewage disposal recommendations : Do not dispose of waste into sewer.

### SECTION 14: Transport information

In accordance with DOT and TDG  
Not considered a dangerous good for transport regulations  
Proper Shipping Name (ADR) : Not applicable

#### Transport by sea

No additional information available

#### Air transport

No additional information available

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

**barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

**Iron oxide red (1309-37-1)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

**4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

**barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

**Iron oxide red (1309-37-1)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

**4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### EU-Regulations

**barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesulphonate] (1103-38-4)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

**Iron oxide red (1309-37-1)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

**4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### National regulations

**LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green**

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

#### 15.3. US State regulations

**Iron oxide red (1309-37-1)**

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

Indication of changes

: Original Document.

Data sources

: ACGIH (American Conference of Government Industrial Hygienists).

European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

# LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green


## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Abbreviations and acronyms : ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.  
CLP: Classification, Labelling, Packaging.  
EC50: Environmental Concentration associated with a response by 50% of the test population.  
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).  
LD50: Lethal Dose for 50% of the test population.  
OSHA: Occupational Safety & Health Administration.  
PBT: Persistent, Bioaccumulative, Toxic.  
TWA: Time Weight Average.  
TSCA: Toxic Substances Control Act.

Other information : None.

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 1 - Must be preheated before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



### Full text of H-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Skin Sens. 1	Sensitisation — Skin, category 1
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

LACO NA GHS SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*