

SAFETY DATA SHEET

Section 1: Product and Company Identification

Product Name: PRO-LINE HP

Product Code:

PRO-LINE HP White (96960)	PRO-LINE HP Silver (96967)
PRO-LINE HP Yellow (96961)	PRO-LINE HP Light Green (96970)
PRO-LINE HP Red (96962)	PRO-LINE HP Light Blue (96971)
PRO-LINE HP Black (96963)	PRO-LINE HP Gold (96972)
PRO-LINE HP Orange (96964)	PRO-LINE HP Pink (96973)
PRO-LINE HP Blue (96965)	PRO-LINE HP Purple (96974)
PRO-LINE HP Green (96966)	PRO-LINE HP Brown (96975)

Product Use: Marker for metal, wood, glass, plastic, rubber, cardboard and paper.


Supplier: LA-CO Industries, Inc.
 1201 Pratt Boulevard
 Elk Grove Village, IL.
 60007-5746
 E-mail Contact: customer_service@laco.com

Phone Number: (847) 956-7600

Fax: (847) 956-9885

24-hour Emergency: CHEMTREC: (800) 424-9300

Section 2: Hazards Identification

Protective Clothing	NFPA Rating (USA)	EC Classification	WHMIS (Canada)	Transport
Not Required for Normal Use		Not Classified as Dangerous	Not Controlled	Not Regulated

Emergency Overview: Normal use of this marker will not result in exposure to hazardous substances. The paint contained inside the marker has components which are flammable and are considered harmful by inhalation of vapors, eye and skin contact.

Appearance, Color and Odor: Marker containing various colored liquid paint. Solvent-like odor.

USA: This product is not a hazardous material as defined by 29 CFR 1910.1200, OSHA Hazard Communication Evaluation. This product meets the definition of an "article".

Canada: This is not a controlled product under WHMIS. This product meets the definition of a "manufactured article" and is not subject to the regulations of the Hazardous Products Act.

European Communities (EC): This product is not classified as dangerous according to Directive 1999/45/EC and its amendments. This product contains a small amount of a liquid preparation which contains dangerous ingredients however, there is no expected release of the liquid during use of the product and there is a barrier preventing exposure of the user and the environment.

Potential Health Effects: ACUTE (short term): see Section 8 for exposure controls

Relevant Route(s) of Exposure: The paint contained inside the marker has components which are considered harmful by inhalation of vapors, eye and skin contact. Exposure to the paint is not expected with normal use of the marker.

Inhalation: Inhalation of vapors is not expected with normal use of the marker.

Ingestion: Not an expected route of exposure.

SAFETY DATA SHEET

Section 2: Hazards Identification (continued)

Skin: Normal use of marker will not result in harmful effects. Contact with the paint may be harmful to the skin; may be absorbed through the skin.

Eye: Not an expected route of exposure. Liquid and vapors can irritate the eyes.

CHRONIC (long term): see Section 11 for additional toxicological data

Long-term health effects not expected with normal use of the marker. Prolonged or repeated contact of the paint to skin may result in defatting and drying of skin and may result in dermatitis. Inappropriate use of the marker resulting in over-exposure by inhalation or ingestion to the paint can have adverse long-term health effects.

Medical Conditions Aggravated by Preexisting skin, eye and respiratory disorders may be aggravated by over-exposure to the Exposure: paint. Impaired central nervous system functions from preexisting disorders may be aggravated by over-exposure to the paints.

Interactions With Other Chemicals: Not available

Potential Environmental Effects: Paint components in marker have exhibited low toxicity in aquatic organisms.

Section 3: Composition / Information on Ingredients

Hazardous Ingredients:

Chemical Name	CAS No.	Wt. %	EINECS / ELINCS	Symbol	Risk Phrases
Cyclohexyl Ketone	108-94-1	20-35	203-631-1	Xn	R10; R20
Methyl Propyl Ketone (MPK)	107-87-9	20-35	203-528-1	Not classified in Annex I	Not classified in Annex I
Ethyl Acetate	141-78-6	0.5 – 1.5	205-500-4	F; Xi	R11; R36; R66; R67

Note: See Section 16 for the full text of the R-phrases above.

Section 4: First Aid Measures

- Inhalation:** If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
- Eye Contact:** No effects expected. If irritation occurs, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
- Skin Contact:** No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
- Ingestion:** If irritation or discomfort occurs, obtain medical advice immediately.

SAFETY DATA SHEET**Section 5: Fire Fighting Measures**

Flammable Properties:	Markers contain a small amount of flammable liquid. Flashpoint for MPK is 8°C (46.4°F), TAG Closed Cup.
Suitable extinguishing Media:	For small fires, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, use carbon dioxide, dry chemical powder, alcohol-resistant foam or polymer foam. Firefighting foams are the extinguishing agent of choice for most flammable liquid fires. Use water spray to cool fire-exposed containers.
Unsuitable extinguishing Media:	Not available
Explosion Data:	
Sensitivity to Mechanical Impact:	Not available
Sensitivity to Static Discharge:	Sensitive: Vapor may be ignited by a static discharge.
Specific Hazards arising from the Chemical:	Combustion may produce toxic and irritating gases. Can form explosive mixtures at or above the flashpoint. Containers can build up pressure if exposed to heat (fire).
Protective Equipment and precautions for firefighters:	Self-contained breathing apparatus and protective clothing should be worn. Vapors may accumulate and travel to ignition sources distant from the handling site. Remove all unauthorized personnel.
NFPA	
	Health: 0
	Flammability: 1
	Instability: 0

Section 6: Accidental Release Measures

Personal Precautions:	Wear protective equipment and ventilate the area.
Environmental Precautions:	Prevent the paint from entering sewers or waterways.
Methods for Containment:	Stop the leak if it is safe to do so. Contain spilled paint with earth, sand, or absorbent material which does not react with spilled material.
Methods for Clean-up:	Soak up spill with an inert absorbent material. Place the contaminated absorbent in a sealed container and dispose according to all applicable regulations.

Section 7: Handling and Storage

Handling:	This product contains a small amount of a flammable liquid. Avoid contact with skin and eyes. Do not use near ignition sources. Keep out of reach of children.
Storage:	Store in a cool, dry area, out of direct sunlight and away from heat, flames and ignition sources. Keep markers tightly closed when not in use.

SAFETY DATA SHEET

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

Measurable airborne concentrations of the component substances, listed in Section 3, are not expected when the markers are used for their intended purpose. Consult local authorities for acceptable exposure limits.

Exposure Controls

Engineering Controls: Provide adequate ventilation to keep vapor concentrations below the exposure limits listed above.

Personal Protection:

Eye/Face Protection: Not required for normal use.

Skin Protection: Not required for normal use. If repeated skin contact is likely wear gloves made of butyl rubber.

Respiratory Protection: Not required for normal use. NIOSH approved respirator for organic vapors in high vapor concentrations.

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or Canadian Standards Association (CSA) Standard Z94.4-93 must be followed whenever workplace conditions warrant a respirator's use.

Other Protective Equipment: Not required.

General Hygiene Measures: Avoid breathing vapors. Do not ingest. Avoid contact with skin and eyes. Keep out of reach of children. Do not smoke while handling this material. Wash hands after handling.

Section 9: Physical and Chemical Properties

Physical State:	Solid marker containing liquid paint.	Flash Point & method:	8°C (46.4°F) for MPK, TAG Closed Cup
Appearance, Color and Odor:	Marker containing liquid paint in various colors. Solvent-like odor.	Autoignition Temperature:	Not available
Odor Threshold:	Not available	Flammability Limits in Air:	LEL: 1.1% UEL: 9.4-11% (for the paints)
pH:	Not applicable	Vapor Pressure:	Not available
Specific Gravity: (water = 1)	0.9 – 1.4	Vapor Density: (Air = 1)	>1.0 (for the paints)
Partition coefficient: (n-octanol/water)	Not available	Evaporation Rate: (n-Butyl Acetate = 1)	>1.0 (for the paints)
Solubility:	Paint is soluble in organic solvents.	Boiling Point/Range:	103°C (217°F) for MPK
Viscosity:	Paint is water thin	Melting Point:	Not available
Decomposition Temperature:	Not available	VOC Content:	50-85% w/w

SAFETY DATA SHEET

Section 10: Stability and Reactivity

Chemical Stability:	Stable at normal room temperature.
Conditions to Avoid:	Avoid heat, open flames, static charge, sparks and ignition sources.
Incompatible Materials:	Incompatible with strong oxidizing agents.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.
Possibility of Hazardous Reactions:	Hazardous polymerization will not occur.

Section 11: Toxicological Information

Acute Toxicity Data

	<u>LD₅₀ Oral</u> (mg/kg)	<u>LD₅₀ Dermal</u> (mg/kg)	<u>LC₅₀ Inhalation</u> (4 hrs.)
Cyclohexyl Ketone	1 340 (rat)	950 (rabbit)	2 639 ppm (rat)
Methyl Propyl Ketone (MPK)	2 205 (mouse)	6 450 (rabbit)	2 000 – 4 000 ppm (rat)
Ethyl Acetate	4 900 (rabbit)	> 18 000 (rabbit)	10 600 ppm (mouse)

Chronic Toxicity Data

Carcinogenicity:	Normal use of this product will not result in exposure to any component that is considered a human carcinogen by IARC (International Agency for Research on Cancer), ACGIH (American Conference of Governmental Industrial Hygienists, OSHA or NTP (National Toxicology Program).
Irritation:	Normal use of marker will not result in harmful effects. Direct eye or skin contact with the paint can cause moderate to severe irritation.
Corrosivity:	Not available
Sensitization:	Not applicable with normal use of the marker.
Neurological Effects:	Not applicable with normal use of the marker.
Genetic Effects:	Not available
Reproductive Effects:	Not applicable with normal use of the marker.
Developmental Effects:	Not applicable with normal use of the marker.
Other Adverse Effects:	Not applicable with normal use of the marker.
Target Organ Effects:	Not applicable

Section 12: Ecological Information

Ecotoxicity:	Paints have exhibited low toxicity in aquatic organisms.
Persistence/Degradability:	Not applicable
Bioaccumulation/Accumulation:	Not applicable
Mobility:	Not available

SAFETY DATA SHEET

Section 13: Disposal Considerations

Waste Disposal Method: Do NOT dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Spent markers are considered "empty" of fluid.

USA: Dispose of in accordance with local, state and federal laws and regulations.
Canada: Dispose of in accordance with local, provincial and federal laws and regulations.
EC: Waste must be disposed of in accordance with relevant EC Directives and national, regional and local environmental control regulations. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

Section 14: Transport Information:

U.S. Hazardous Materials Regulation (DOT 49CFR): This product conforms to 49 CFR 173.4 for domestic highway or rail transport only.
 Conforms to 49 CFR 173.4a Excepted quantity of Class 3 Flammable liquid.

Canadian Transportation of Dangerous Goods (TDG): Dangerous goods in excepted quantity.

ADR/RID: Dangerous goods in excepted quantity.

IMDG: Dangerous goods in excepted quantity.

Marine Pollutants: Not applicable

ICAO/IATA: Dangerous goods in excepted quantity.

Section 15: Regulatory Information

USA

TSCA Status: All ingredients in the product are listed on the TSCA inventory.

SARA Title III

Sec. 302/304: None
 Sec: 311/312: Not applicable
 Sec. 313: None

CERCLA RQ: Cyclohexyl Ketone 5 000 lb, Ethyl Acetate 5 000 lb

California Prop 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

State Right-to-Know Lists : Cyclohexyl Ketone, Methyl Propyl Ketone, Ethyl Acetate, Carbon black and Titanium dioxide can be found on the following state right to know lists: Massachusetts, New Jersey, Pennsylvania.

Canada

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

WHMIS Classification: Not controlled
 (for workplace exposures)

NSNR Status: All ingredients in the product are listed, as required, on Canada's Domestic Substances List (DSL).

NPRI Substances: Ethyl Acetate is a NPRI reportable substance.

EC Classification for the Substance/Preparation

Symbol: This product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Risk Phrases: None

Safety Phrases: S2: Keep out of reach of children.

SAFETY DATA SHEET**Section 16: Other Information****Full Text of R-phrases appearing in Section 2:**

R10: Flammable.
R11: Highly flammable.
R20: Harmful by inhalation.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapors may cause drowsiness and dizziness.

Preparation Information:**Revision Date:**

September 29, 2014

Revision Summary:

Section 8: Skin protection. Section 3: Ingredient composition.

Supplier Disclaimer:

The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, LA-CO Industries, Inc. makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will LA-CO Industries, Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

Prepared by:

LEHDER Environmental Services Limited (519) 336-4101
www.lehder.com

While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.